

1999 to 2004 Model Year Suggested Service Intervals Summary: FD46TA and FE6TA Engines and Powertrain

Engine Oil Change Intervals

Engine	Interval with API CF-4 Engine Oil
FD46TA	4 months / 10,000 miles*
FE6TA	4 months / 10,000 miles*
* whichever occurs first	

SAE Viscosity = selected by temperature, see Service Manual CD or Owner's Manual charts

Transmission / Differential / Long Life Antifreeze Service Interval:

Vehicle Model	Trans Type	Service Interval	Fluid / Oil Specification
1300 / 1400	Aisin-Seiki ATM	12 months / 25,000 miles*	Dexron III
1300 / 1400	MES50 Manual	12 months / 20,000 miles*	API GL-4 90w
1300 / 1400	Differential	12 months / 20,000 miles*	API GL-5 (see viscosity chart in Svc Manual)
1300 / 1400	Long Life Antifreeze	24 months / 185,000 miles*	UD Genuine Long Life Antifreeze Coolant Part # IN6001 or equivalent
1800CS	Aisin-Seiki ATM	12 months / 25,000 miles*	Dexron III
1800CS	MHS Manual	12 months / 30,000 miles*	API GL-4 90w
1800CS	Differential	12 months / 30,000 miles*	API GL-5 (see viscosity chart in Svc Manual)
1800CS	Long Life Antifreeze	24 months / 185,000 miles*	UD Genuine Long Life Antifreeze Coolant Part # IN6001 or equivalent
1800HD - 3300	Allison ATM	24 months / 50,000 miles*	Dexron III
1800HD - 3300	MLS Manual	12 months / 30,000 miles*	API GL-4 90w
1800HD - 3300	Differential	12 months / 30,000 miles*	API GL-5 (see viscosity chart in Svc Manual)
1800HD - 3300	Long Life Antifreeze	24 months / 185,000 miles*	UD Genuine Long Life Antifreeze Coolant Part # IN6001 or equivalent
* whichever occurs first			